



Medium Combat Truck

3½ Ton Eight Wheel Rough Terrain Truck — Adaptable to dozens of configurations for hundreds of applications. From ambulance to container handler to wrecker, the MCT is a virtual workhorse. With top speeds in excess of 55 m.p.h. and true tactical mobility, both its hydrostatic drive/braking and independent wheel height controls are innovative functions of Standard's Trailing Arm Drive (TAD™).



Specifications

Vehicle Weight 12,000 lbs.
Payload Capacity 7,000 lbs.
Gross Vehicle Weight 20,000 lbs.

Cab Capacity Driver + 2 Passengers

Drive System All-Wheel Hydrostatic

Suspension System 8-Wheel Independent
Trailing Arm Drive™

Steering Automotive-Type Control With
Counterrotation Capability

Overall Dimensions:

Length 235 in.
Width 96 in.
Bed Height (variable) 41 in. Kneeled
50 in. Raised
Height (variable) 103 in. Kneeled
111 in. Raised

Air Transportability Air-Transportable in C-130 Aircraft

Speed Ranges:

1st — Severe Terrain 0-6 mph
2nd — Rough Terrain 0-13 mph

3rd — Cross Country 0-21 mph
4th — Maintained Surfaces 0-55 mph

Brakes Hydrostatic Braking and Air
Over Hydraulic Disc Brakes

Lights Combat Service and Blackout Lights

Engine:

Model Cummins 6BT5.9
Type 4 Cycle, 6 Cylinder Diesel
Horsepower 160 hp @ 2800 rpm
Fuel Tank Capacity 50 gal

Optional Engine:

Model Cummins 6BTA5.9
Horsepower 186 hp @ 2800 rpm

Tires Super All-Traction 14-17.5,8PR
Tire Pressure Max. Inflation Pressure 70 psi

Ground Pressure 6.84 psi

Slope Negotiation:

Longitudinal 60%
Sideslope 30%

Towing Capability Vehicle of Equal Weight

Standard Manufacturing Company, Inc.

4012 W. Illinois Ave. P.O. Box 210300

Dallas, Texas USA 75221 Phone 214/337-8911 Telex 73326

Serving Armed Forces Worldwide for Four Decades